SECONDARY DUST SEAL®

- ✓ Simple Installation
- ✓ Low Maintenance
- Corrosion Resistant
- ✓ Fast Delivery





- Simple and effective way to seal in fugitive dust.
- Works in unison with your existing skirt rubber to maximize sealing efficiency.
- Improves the effectiveness of your skirting by acting as a secondary barrier to harmful (and costly) spillage.
- Easily installed by tying each end of the rope.
- Maintenance free.
- Inexpensive way to improve sealing.
- · Manual adjustments not needed.
- Wear-resistant EPDM rubber makes the Secondary Dust Seal virtually indestructible.



WHO IS ARCH ENVIRONMENTAL?

Manufacturer and worldwide distributor of preferred bulk conveyor components since 1975.





800.553.4567 www.archenv.com

MECHANICAL DIVISION

Belt Cleaners • Belt Alignment • Sealing Systems
Dust Control Systems • Impact/Slider Systems

ELECTRICAL DIVISION

Belt Scales • Metal Detectors • Pull Cord Switches Belt Protection Devices • Conveyor Control Systems

SECONDARY DUST SEAL®

TEMP. RANGE: -40C to +107C (225F) CONTINUOUS +121C(+250F) SHORT TERM

MATERIAL: BLACK EPDM RUBBER

EXCELLENT RESISTANCE TO OZONE, UV, AND WEATHER

HARDNESS: 55-65 SHORE A

APPROXIMATE WEIGHT: 1.5 pounds per foot

SUPPLIED IN CONTINUOUS LENGTHS UP TO 350 FEET



